

UGL® 222 Spackling Paste

MANUFACTURER

UNITED GILSONITE LABORATORIES

MAILING: P.O. Box 70, Scranton, Pennsylvania, 18501

SHIPPING: 1396 Jefferson Avenue, Dunmore, Pennsylvania, 18509

TOLL FREE: 1-800-UGL-LABS (845-5227)

PHONE: 1-570-344-1202 • FAX: 1-570-969-7634

www.ugl.com



PRODUCT DESCRIPTION

UGL 222 Spackle is an all-purpose patching compound for interior or exterior use. This dust control formula will allow for faster cleanup and less mess. Ideal for patching cracked plaster, filling nail holes, and smoothing surface imperfections on drywall and wood. UGL Spackling Paste is a non-shrinking formula that sands easily.

- All purpose patching compound
- Repair nail holes
- Smooth surface imperfections
- Dust control formula

BASIC USES

The product is ideal for patching cracked plaster, filling nail holes and smoothing surface imperfections on drywall and wood.

TECHNICAL DATA

COMPOSITION:

Vinyl acrylic

SHEEN:

N/A

% WEIGHT SOLIDS:

71.8%

% VOLUME SOLIDS:

51.7%

DENSITY (LBS./US GAL.):

14

VISCOSITY:

Stiff paste

pH:

8+

COLORS:

White

DRY TIME:

• 2 hours

Note: Maximum cure and dry time will

be prolonged when slightly humid and damp, cool conditions prevail.

CLEAN UP:

Soap and water

Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

COVERAGE (CU. IN./US QT.):

• 56 cu. in./qt.

Note: Actual coverage will vary depending upon application method, surface texture and porosity.

RECOMMENDED FILM THICKNESS/COAT:

N/A

FLASH POINT:

N/A

SHELF LIFE:

N/A

FREEZE/THAW:

Keep from freezing

CONTAINER SIZES:

One-half pint (US), one quart (US) containers

VOC

N/A

TINTING

N/A

SURFACE PREPARATION

Remove all loose dirt and scaly or powdery material. All metal, including nail heads, should be primed with a metal primer. UGL 222 Spackling Paste and surface temperature of area to be patched must be above 50°F. All exterior applications must be painted.

WARNING

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

APPLICATION

Apply with a putty knife or broad knife. Deep cracks should be filled in two steps, allowing the material to dry thoroughly between applications.

UGL 222 Spackling Paste can be painted over immediately after drying with any type of decorative finish.

CAUTION

Prolonged contact with skin during mixing or application may cause irritation some cases. If splashed on skin or in eyes, flush thoroughly with water.

This product contains a chemical(s) known to the State of California to cause cancer and birth defects or other reproductive harm.

DO NOT TAKE INTERNALLY.
AVOID BREATHING DUST
KEEP OUT OF REACH OF CHILDREN

FIRST AID

EYES: Immediately flush eye thoroughly with



DRY TIME:
2 Hours



CLEAN-UP:
Soap and Water



COVERAGE:
1 Application, 2
for Deeper Patch



SPREAD RATE:
56 Cu. In./Qt.

water for at least 15 minutes. Consult a physician if irritation persists.

SKIN: Wash affected area with soap and water. Consult a physician if irritation is present.

INGESTION: Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth. Place individual on the left side with head down. Contact a physician, medical facility or poison control center for advice about whether to induce vomiting.

INHALATION: Remove to fresh air.

For additional health and safety information please refer to the "Materials Safety Data Sheet".

WARRANTY

N/A

SPECIFICATION

N/A



222 Spackling Paste

1/2 PT.	6/Case	31706
1 QT.	6/Case	31712

DISCLAIMER: This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of UGL's knowledge, or obtained from sources believed by UGL to be accurate, and UGL does not assume any legal responsibility for use or reliance upon same. Before using any product, read the label.