

ZAR® SB Semi-Transparent Deck and Siding - Oak Brown

Version number: REV 1.0

Date of compilation: 2021-10-14

SECTION 1: Identification

1.1 Product identifier

Trade name **ZAR® SB Semi-Transparent Deck and Siding - Oak Brown**

Alternative number(s) 67613; UFI: YRD1-NGE0-4M0E-P3M1
67615; UFI: YRD1-NGE0-4M0E-P3M1

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses stain
paint related material

1.3 Details of the supplier of the safety data sheet

United Gilsonite Laboratories, Inc.
1396 Jefferson Avenue
Dunmore PA 18509
United States

Telephone: +1 (570) 344-1202
Telefax: (570) 969-7634
e-mail: sales@ugl.com
Website: <http://www.ugl.com/>

e-mail (competent person) nicholas.shaffmaster@ugl.com (Nicholas Shaffmaster)

1.4 Emergency telephone number

Emergency information service 1-800-424-9300 Chemtrec (NORTH AMERICA)
Emergency telephone number: outside office hours

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.4S	skin sensitization	1	Skin Sens. 1	H317
A.6	carcinogenicity	1A	Carc. 1A	H350
A.10	aspiration hazard	1	Asp. Tox. 1	H304
B.6	flammable liquid	3	Flam. Liq. 3	H226

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

- Pictograms

ZAR® SB Semi-Transparent Deck and Siding - Oak Brown

Version number: REV 1.0

Date of compilation: 2021-10-14

GHS02, GHS07, GHS08



- Hazard statements

H226	Flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H350	May cause cancer.

- Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P201	Obtain special instructions before use.
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
P272	Contaminated work clothing must not be allowed out of the workplace.
P280	Wear protective gloves/eye protection/face protection.
P301+P310	If swallowed: Immediately call a poison center/doctor.
P302+P352	If on skin: Wash with plenty of water.
P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P308+P313	If exposed or concerned: Get medical advice/attention.
P321	Specific treatment (see on this label).
P331	Do NOT induce vomiting.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P363	Wash contaminated clothing before reuse.
P370+P378	In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to industrial combustion plant.

- Hazardous ingredients for labelling

Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-[3-[3-(2 H-benzotriazol-2-yl)-5-(1,1- dimethylethyl)-4-hydroxyphenyl]-1- oxopropoxy]-, Carbon black, Dis-
tillates (petroleum), hydrotreated light, Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-hydroxy-

2.3 Other hazards

Hazards not otherwise classified

Contains Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-[3-[3-(2 H- benzotriazol-2-yl)-5-(1,1- dimethylethyl)-4-hydroxyphenyl]-1- oxopropoxy]-, Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-hydroxy-. May produce an allergic reaction.
May be harmful in contact with skin (GHS category 5: acutely toxic - dermal).
May be harmful if inhaled (GHS category 5: acutely toxic - inhalation).
Harmful to aquatic life with long lasting effects (GHS category 3: aquatic toxicity - acute and/or chronic).

ZAR® SB Semi-Transparent Deck and Siding - Oak Brown

Version number: REV 1.0

Date of compilation: 2021-10-14

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS
Distillates (petroleum), hydro-treated light	CAS No 64742-47-8	10 - < 25	Acute Tox. 3 / H331 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226
Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-[3-[3-(2 H-benzotriazol-2-yl)-5-(1,1- dimethyl-ethyl)-4-hydroxyphenyl]-1- oxoproxy]-	CAS No 104810-47-1	0.05 - < 1	Skin Sens. 1 / H317
Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2- yl)-5- (1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-hydroxy-	CAS No 104810-48-2	0.05 - < 1	Skin Sens. 1 / H317
Naphtha (petroleum), hydro-treated heavy	CAS No 64742-48-9	0.05 - < 1	Acute Tox. 3 / H331 STOT SE 3 / H336 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226
Carbon black	CAS No 1333-86-4	0.05 - < 1	Carc. 1A / H350

For full text of abbreviations: see SECTION 16.

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

ZAR® SB Semi-Transparent Deck and Siding - Oak Brown

Version number: REV 1.0

Date of compilation: 2021-10-14

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO₂)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Nitrogen oxides (NO_x), Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

ZAR® SB Semi-Transparent Deck and Siding - Oak Brown

Version number: REV 1.0

Date of compilation: 2021-10-14

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

- Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	diiiron trioxide (iron(III) oxide)	1309-37-1	TLV®		5					r	ACGIH® 2021
US	iron(III) oxide	1309-37-1	PEL (CA)		5					fume	Cal/ OSHA PEL
US	iron(III) oxide	1309-37-1	PEL		10					fume	29 CFR 1910.10 00
US	iron(III) oxide (diiiron trioxide)	1309-37-1	REL		5 (10 h)					df, Fe	NIOSH REL

ZAR® SB Semi-Transparent Deck and Siding - Oak Brown

Version number: REV 1.0

Date of compilation: 2021-10-14

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	rouge	1309-37-1	REL							appx-D	NIOSH REL
US	rouge	1309-37-1	PEL		15					i, dust	29 CFR 1910.1000
US	rouge	1309-37-1	PEL		5					r, dust	29 CFR 1910.1000
US	carbon black	1333-86-4	PEL (CA)		3.5						Cal/OSHA PEL
US	carbon black	1333-86-4	PEL		3.5						29 CFR 1910.1000
US	carbon black	1333-86-4	REL		3.5 (10 h)					appx-A, appx-C	NIOSH REL
US	carbon black	1333-86-4	TLV®		3					i	ACGIH® 2021
US	Carbon black in presence of polycyclic aromatic hydrocarbons (PAHs)	1333-86-4	REL		0.1 (10 h)					PAHs, appx-A, appx-C	NIOSH REL
US	petroleum distillates (naphtha) (rubber solvent)	64742-48-9	PEL	500	2,000						29 CFR 1910.1000
US	mineral oil	8042-47-5	TLV®		5					i, ex-Met-WorkFl	ACGIH® 2021

Notation

- appx-A NIOSH Potential Occupational Carcinogen (Appendix A)
- appx-C Appendix C - Supplementary Exposure Limits
- appx-D see Appendix D - Substances with No Established RELS
- Ceiling-C ceiling value is a limit value above which exposure should not occur
- df as dust and fumes
- dust as dust
- exMetWork-Fl excluding metal working fluids
- Fe calculated as Fe (iron)
- fume as fume
- i inhalable fraction
- PAHs as polycyclic aromatic hydrocarbons (PAHs)
- r respirable fraction
- STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
- TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours
time-weighted average (unless otherwise specified)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

ZAR® SB Semi-Transparent Deck and Siding - Oak Brown

Version number: REV 1.0

Date of compilation: 2021-10-14

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid
Color	not determined
Particle	not relevant (liquid)
Odor	characteristic

Other safety parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	≥146 °C at 101.3 kPa
Flash point	39 °C at 1 atm
Evaporation rate	not determined
Flammability (solid, gas)	not relevant, (fluid)
Vapor pressure	≤3.7 kPa at 37.8 °C
Density	0.917 g/cm ³ at 25 °C
Vapor density	this information is not available
Solubility(ies)	not determined

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
-----------------------------	-----------------------------------

ZAR® SB Semi-Transparent Deck and Siding - Oak Brown

Version number: REV 1.0

Date of compilation: 2021-10-14

Auto-ignition temperature	220 °C (auto-ignition temperature (liquids and gases))
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains re-active substance(s). Risk of ignition.

If heated:

Risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4: May be harmful in contact with skin or if inhaled.

Acute toxicity estimate (ATE) of components of the mixture			
Name of substance	CAS No	Exposure route	ATE
Distillates (petroleum), hydrotreated light	64742-47-8	inhalation: vapor	>5.28 mg/l/4h
Naphtha (petroleum), hydrotreated heavy	64742-48-9	inhalation: vapor	>9.3 mg/l/4h

ZAR® SB Semi-Transparent Deck and Siding - Oak Brown

Version number: REV 1.0

Date of compilation: 2021-10-14

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

May cause an allergic skin reaction.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

May cause cancer.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans

Name of substance	CAS No	Classification	Number
Carbon black	1333-86-4	2B	

Legend

2B Possibly carcinogenic to humans

National Toxicology Program (United States): Report on Carcinogens

Name of substance	CAS No	Classification	Number
Carbon black	1333-86-4	Known to be human carcinogens	1st Report on Carcinogens

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Distillates (petroleum), hydrotreated light	64742-47-8	LL50	5 mg/l	fish	96 h
Distillates (petroleum), hydrotreated light	64742-47-8	EL50	1.4 mg/l	aquatic invertebrates	48 h

ZAR® SB Semi-Transparent Deck and Siding - Oak Brown

Version number: REV 1.0

Date of compilation: 2021-10-14

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]-	104810-47-1	LC50	2.8 mg/l	fish	96 h
Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]-	104810-47-1	EC50	4 mg/l	aquatic invertebrates	48 h
Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-hydroxy-	104810-48-2	LC50	2.8 mg/l	fish	96 h
Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-hydroxy-	104810-48-2	EC50	4 mg/l	aquatic invertebrates	48 h
Naphtha (petroleum), hydrotreated heavy	64742-48-9	LL50	>1,000 mg/l	fish	24 h
Naphtha (petroleum), hydrotreated heavy	64742-48-9	EL50	>1,000 mg/l	aquatic invertebrates	24 h
Carbon black	1333-86-4	EC50	>5,600 mg/l	aquatic invertebrates	24 h
Carbon black	1333-86-4	ErC50	>10,000 mg/l	algae	72 h

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Distillates (petroleum), hydrotreated light	64742-47-8	EL50	0.89 mg/l	aquatic invertebrates	21 d
Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]-	104810-47-1	LC50	3.8 mg/l	fish	4 d

ZAR® SB Semi-Transparent Deck and Siding - Oak Brown

Version number: REV 1.0

Date of compilation: 2021-10-14

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-hydroxy-	104810-47-1	EC50	>0.78 mg/l	aquatic invertebrates	21 d
Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-hydroxy-	104810-48-2	LC50	3.8 mg/l	fish	4 d
Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-hydroxy-	104810-48-2	EC50	>0.78 mg/l	aquatic invertebrates	21 d

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

None of the ingredients are listed.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

ZAR® SB Semi-Transparent Deck and Siding - Oak Brown

Version number: REV 1.0

Date of compilation: 2021-10-14

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number

DOT	UN 1263
IMDG-Code	UN 1263
ICAO-TI	UN 1263

14.2 UN proper shipping name

DOT	Paint
IMDG-Code	PAINT
ICAO-TI	Paint

14.3 Transport hazard class(es)

DOT	3
IMDG-Code	3
ICAO-TI	3

14.4 Packing group

DOT	III
IMDG-Code	III
ICAO-TI	III

14.5 Environmental hazards

non-environmentally hazardous acc. to the dangerous goods regulations

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

Particulars in the shipper's declaration	UN1263, Paint, 3, III
Reportable quantity (RQ)	201,207 lbs (91,348 kg) (xylene) (formaldehyde)
Danger label(s)	3



Special provisions (SP)	367, B1, B52, B131, IB3, T2, TP1, TP29
ERG No	128

ZAR® SB Semi-Transparent Deck and Siding - Oak Brown


Version number: REV 1.0

Date of compilation: 2021-10-14

International Maritime Dangerous Goods Code (IMDG) - Additional information

Marine pollutant	-
Danger label(s)	3
	
Special provisions (SP)	163, 223, 367, 955
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
EmS	F-E, <u>S-E</u>
Stowage category	A

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Danger label(s)	3
	
Special provisions (SP)	A3, A72, A192
Excepted quantities (EQ)	E1
Limited quantities (LQ)	10 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Toxic Substance Control Act (TSCA) all ingredients are listed

Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
Naphtha (petroleum), hydrotreated heavy	64742-48-9		Canada PBITs EC Annex VI CMRs - Cat. 1B
Carbon black	1333-86-4		IARC Carcinogens - 2B Prop 65

- Hazardous Substances List (MN-ERTK)

Name of substance	CAS No	References	Remarks
Carbon black	1333-86-4	A, N, O, R, *	

Legend

- * Substances which are regulated by OSHA as carcinogens; have been categorized by the ACGIH as either "human carcinogens" or "suspect of carcinogenic potential for man"; have been evaluated by the International Agency for Research on Cancer (IARC) and found to be carcinogens or potential carcinogens; or have been listed as a carcinogen or potential carcinogen in the Annual Report on Carcinogens published by the National Toxicology Program (NTP).
- A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH
- N National Institute for Occupational Safety and Health (NIOSH), "Recommendations for Occupational Safety and Health Standards," August 1988, available from NIOSH, Publications Dissemination Office, Division of Standards Development and Technology Transfer
- O Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division

ZAR® SB Semi-Transparent Deck and Siding - Oak Brown

Version number: REV 1.0

Date of compilation: 2021-10-14

Legend

R International Agency for Research on Cancer (IARC) Monographs on the Evaluation of the Carcinogenic Risks to Humans; Overall Evaluations of Carcinogenicity: An Updating of IARC Monographs Volumes 1 to 42, Supplement 7 (1987). Available from: WHO Publications Centre USA

- Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
Carbon black	1333-86-4		CA

Legend

CA Carcinogenic

- Hazardous Substance List (Chapter 323) (PA-RTK)

Name acc. to inventory	CAS No	Classification
SOOT		S

Legend

S Special hazardous substance

- Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
Carbon black	1333-86-4	T

Legend

T Toxicity (ACGIH®)

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals			
Name acc. to inventory	CAS No	Remarks	Type of the toxicity
silica, crystalline		airborne particles of respirable size	cancer
carbon black	1333-86-4	airborne, unbound particles of respirable size	cancer
ethylbenzene	100-41-4		cancer
formaldehyde	50-00-0	gas	cancer
ethylene glycol monoethyl ether	110-80-5		developmental, male
ethylene glycol monomethyl ether	109-86-4		developmental, male

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

ZAR® SB Semi-Transparent Deck and Siding - Oak Brown

Version number: REV 1.0

Date of compilation: 2021-10-14

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	2	temporary or minor injury may occur
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
US	TSCA	all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
AU	AICS	all ingredients are listed
CA	DSL	not all ingredients are listed
CA	NDSL	not all ingredients are listed
CN	IECSC	not all ingredients are listed
EU	ECSI	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	not all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed

Legend

AICS Australian Inventory of Chemical Substances
 CICR Chemical Inventory and Control Regulation
 CSCL-ENCS List of Existing and New Chemical Substances (CSCL-ENCS)
 DSL Domestic Substances List (DSL)

ZAR® SB Semi-Transparent Deck and Siding - Oak Brown

Version number: REV 1.0

Date of compilation: 2021-10-14

Legend

ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NDSL	Non-domestic Substances List (NDSL)
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H226	Flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H350	May cause cancer.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

End of safety data sheet