



COVERAGE

100 square feet per quart



COATS

Recommended



DRY TIME

12 - 24 hours Recoat 12 hours



CLEAN-UP

Mineral spirits

Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

PRODUCT DATA SHEET

Publication Date: 10-6-21

ZAR® Interior Oil Base Gold Liquid Leaf Paint

PRODUCT DESCRIPTION

LIQUID LEAF PAINT is an interior oil base gold leaf finish for decorative use where the richness and beauty of gold is desired. Add romantic elegant touch or accent to any surface

- Brilliant gold leaf-like finish
- Ideal for indoor decorative use such as crafts, picture frames, toys, restoration projects, furniture trim, and more
- Adhesion to multiple substrates
- · Remains stable, will not tarnish in the container

BASIC USES

This one-step, brush-on, long lasting finish is ideal for picture frames, knick-knacks, furniture trim, crafts, etc. Use on wood, metal, glass, ceramics, paper, plaster, or plastic.

TECHNICAL DATA

COMPOSITION: Oil base

SHEEN: N/A

% WEIGHT SOLIDS: 51 ± 2%

DENSITY (LBS./US GAL.): 8.26 (0.990 SG)

VISCOSITY: 80 ± 5 seconds ford #4 @ 77°F (25°C)

pH: N/A

COLOR:

Gold

DRY TIME:

Recoat 24 hours.

Note: Maximum cure and dry time will be prolonged when slightly humid and damp, cool conditions prevail.

COVERAGE:

100 sq. ft. (9.2m²)/qt.

Note: Actual coverage will vary depending upon application method, surface texture, and porosity.



RECOMMENDED FILM THICKNESS/COAT:

13-21 wet-film-thickness

SHELF LIFE: 5 years unopened container **FREEZE/THAW:** Protect from freezing

CONTAINER SIZES: 1/2 pint and 1 quart

containers

VOC

Does not exceed 500 g/L

TINTING

N/A

LIMITATIONS

Professional use only.

SURFACE PREPARATION

Surface to be painted should be clean and free from all dirt, grease, wax, etc. If your surface has intricate detail areas that show dirt use a scrub brush to get into all the crevices. In some cases your surface may need a white primer for added precaution.

APPLICATION

Apply evenly with a good,soft bristle brush. Brush on paint using minimum pressure, making sure the final brush strokes are made toward the previously applied paint. A second coat may be applied after 24 hours drying time. For spraying, reduce 10 percent with pure turpentine. Allow to dry 24 hours between coats. Temperature, humidity, and film thickness may affect drying time. If while sanding, sandpaper gums or surface feels tacky, extend drying times. Clean brushes with turpentine. To avoid spontaneous combustion during temporary storage,soak soiled rags and wastes immediately after use in a water-filled closed metal container.

WARNING

If you scrape, sand, or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear a NIOSH-approved respirator to control lead exposure.

Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

MAINTENANCE

N/A

CAUTION

CONTAINS PETROLEUM DISTILLATE. VAPOR

HARMFUL. Keep away from heat and flame. May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, nose, throat and skin irritation. Overexposure may cause kidney damage. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSHapproved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Close container after use.

DANGER - RAGS, STEEL WOOL, OR WASTE SOAKED WITH THIS PRODUCT MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER USE, PLACE RAGS, STEEL WOOL, OR WASTE IN A SEALED, WATER-FILLED METAL CONTAINER.

KEEP OUT OF REACH OF CHILDREN.



FIRST AID

In case of eye contact, flush immediately with plenty of water for at least 15 minutes and call a physician immediately; for skin, wash thoroughly with soap and water. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician immediately. If swallowed, do not induce vomiting. Call a physician immediately.

MARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

For additional health and safety information, please refer to the Safety Data Sheet (SDS).

ZAR® is a registered trademarks of United Gilsonite Laboratories (UGL).

DISCLAIMER: This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of UGL's knowledge, or obtained from sources believed by UGL to be accurate, and UGL does not assume any legal responsibility for use or reliance upon same. Before using any product, read the label.

	CONTAINER	NUMBER/CASE	COLOR	ORDER NUMBER
ZAR® Interior Oil Base Gold Liquid Leaf Paint	1/2 pint	6/case	Gold	23506
ZAR® Interior Oil Base Gold Liquid Leaf Paint	1 quart	1/case	Gold	23512



1-800-845-5227 • Fax 1-570-969-7634 • www.ZAR.com