

ZAR® Interior Oil Base Poly PRO

MANUFACTURER

UNITED GILSONITE LABORATORIES

MAILING: P.O. Box 70, Scranton, Pennsylvania, 18501

SHIPPING: 1396 Jefferson Avenue, Dunmore, Pennsylvania, 18509

TOLL FREE: 1-800-UGL-LABS (845-5227)

PHONE: 1-570-344-1202 • FAX: 1-570-969-7634

www.UGL.com



PRODUCT DESCRIPTION

ZAR® Interior Oil Base Poly PRO is a fast drying contractor formula which is perfect for floors, furniture, cabinets, and woodwork. It provides beautiful, long-lasting protection for all types of interior wood. It self-levels and gives superior protection in fewer coats.

- Fast drying contractor formula
- Residential and commercial use
- Self-leveling for a superior finish
- Low odor resin technology

BASIC USES

A fast drying polyurethane finish for floors, furniture, paneling, cabinets, counter tops and woodwork.

LIMITATIONS

For interior use only. Do not apply over wood fillers or finishes containing wax or stearates. Do not thin.

TECHNICAL DATA

COMPOSITION:

Oil base

SHEEN:

- Gloss >90% @ 60°
- Satin 45 ± 3 @ 60°
- Matte 20 ± 3 @ 60°

% WEIGHT SOLIDS:

40 ± 1

DENSITY (LBS./US GAL.):

7.3-7.4 (S.G. 0.87)

VISCOSITY:

A-1 – A-2 Gardner bubble

pH:

N/A

DRY TIME:

- To touch: 30 minutes - 1 hour

- To recoat: 2 hours
- Light use: 24 hours
- Moderate use: 3-5 days
- Maximum use: 7 days

Note: Maximum cure and dry time will be prolonged when slightly humid and damp, cool conditions prevail.

CLEAN UP:

Paint thinner or mineral spirits
Dispose of contaminated absorbent, container and unused contents in accordance with local, state, and federal regulations.

COVERAGE (SQ. FT./GAL.):

400-500 sq. ft. (37.1 m²-46 m²)/gal @ 1 mil

Note: Actual coverage will vary depending upon application method, surface texture, and porosity.

RECOMMENDED FILM THICKNESS/COAT:

2 wet mils/coat

FLASH POINT:

104°F, (40°C)

SHELF LIFE:

5 Years unopened container

FREEZE/THAW:

N/A

CONTAINER SIZES:

One quart (946 mL) and one gallon (3,785 L) cans

VOC

Does not exceed 550 g/L

TINTING

N/A

THINNING

Do not thin.

SURFACE PREPARATION

New Wood: Sand smooth using fine sandpaper. Remove sanding dust with a tack cloth or cloth dampened with paint thinner or mineral spirits.

If open-grained woods are to be filled, use a filler that does not contain stearates or waxes such as ZAR® Wood Patch or ZAR® Trowelable Wood Patch.

Old Clear Finishes in Good Condition:

Remove grease, dirt, and wax. Sand lightly in the direction of the grain to remove any gloss. Clean sanding dust with a tack cloth or cloth dampened with paint thinner or mineral spirits to remove any remnants of dust prior to application and allow to dry.

Old Clear Finishes in Poor Condition, Lacquer or Shellac:

Remove completely. If the old finish contains wax, regardless of condition, remove completely. Sand and remove sanding dust with a tack cloth or cloth dampened with paint thinner or mineral spirits.

Test ZAR® Interior Oil Base Poly PRO in an inconspicuous area for compatibility.


WARNING

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information



DRY TIME:

1-2 Hours
Recoat 2 Hours



CLEAN-UP:

Paint Thinner or Mineral Spirits



COVERAGE:

2 Coats



SPREAD RATE:

400-500 Sq. Ft./Gallon

Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

APPLICATION

Stirring not required for Gloss. For Satin and Matte stir thoroughly before and during application. Do not shake! Do not thin, apply straight from the can. Best applied when air and surface temperatures are between 65°F (18°C) and 85°F (29°C) and the relative humidity is between 40% and 60%. Apply straight from the can. May be applied by brush, lambswool applicator, pad, or sprayer. Flow ZAR® Interior Oil Base Poly PRO on in the direction of the grain. Sand lightly between coats. Remove all sanding dust with a vacuum or tack cloth. If more than 24 hours elapse between coats clean thoroughly. Allow a dry time of up to 2 hours between coats. If while sanding, sandpaper gums or surface feels tacky, extend drying times.

Dries to the touch in 30 minutes to 1 hour-recoat in 2 hours. Temperature, humidity, and film thickness may affect drying time. If while sanding, sandpaper gums or surface feels tacky, extend drying times.

CAUTION

CONTAINS PETROLEUM DISTILLATE. VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE, OR NAUSEA. CAUSES EYE, SKIN, NOSE, AND THROAT IRRITATION.

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Keep away from heat and flame. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

Use only with adequate ventilation. Do not breathe vapors. Ensure fresh air entry during application and drying. If you experience eye watering, headache, or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted

respirator (NIOSH-approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, on skin, or clothing. Wash thoroughly after handling.


FIRST AID

In case of eye contact, flush immediately with plenty of water for at least 15 minutes and call poison control center, hospital emergency room, or physician immediately; for skin, wash thoroughly with soap and water. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, call poison control center, hospital emergency room, or physician immediately. If swallowed, do not induce vomiting. Call poison control center, hospital emergency room, or physician immediately.

KEEP OUT OF REACH OF CHILDREN.

If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

DANGER – RAGS, STEEL WOOL, OR WASTE SOAKED WITH PRODUCT MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER USE, PLACE RAGS, STEEL WOOL, OR WASTE IN A SEALED, WATER-FILLED METAL CONTAINER.

 **WARNING:** Cancer and Reproductive Harm – www.P65Warnings.ca.gov.

For additional health and safety information please refer to the "Safety Data Sheet".

ZAR® is a registered trademark of United Gilsonite Laboratories (UGL).



Interior Oil Base
Poly PRO

1 QT.+ 4/Case33112
1 GAL.+ 2/Case33113

Gloss

Satin

33212
33213

Matte

33512
33513

+ Regionally VOC restricted

DISCLAIMER: This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of UGL's knowledge, or obtained from sources believed by UGL to be accurate, and UGL does not assume any legal responsibility for use or reliance upon same. Before using any product, read the label.