

**ZAR® Paint and Varnish Remover** Eco-Friendly Formula**MANUFACTURER****UNITED GILSONITE LABORATORIES****MAILING:** P.O. Box 70, Scranton, Pennsylvania, 18501**SHIPPING:** 1396 Jefferson Avenue, Dunmore, Pennsylvania, 18509**TOLL FREE:** 1-800-UGL-LABS (845-5227)**PHONE:** 1-570-344-1202 • **FAX:** 1-570-969-7634**www.ugl.com****PRODUCT DESCRIPTION**

ZAR® Semi-Paste Formula Paint and Varnish Remover is a biodegradable, nonflammable stripper ideal for the removal of all types of paints, polyurethanes, two-component epoxy coatings, light industrial and marine grade finishes.

- Rapid penetration (works on multiple surfaces without damaging the surface)
- Heavy duty strength
- Easy to apply semi-paste
- Removes latex and oil based paints, lacquers, varnishes, polyurethanes and two-component epoxy coatings
- Horizontal and vertical use
- Nonflammable, biodegradable
- Does not contain ozone depleting chemicals
- Soap and water cleanup
- 0 VOC

**BASIC USES**

This semi-paste formula is perfect for use on horizontal and vertical surfaces including, wood, metal, fiberglass, glass, masonry, brick and concrete.

**LIMITATIONS**

Two-component epoxy coatings and masonry waterproofing paints may take several applications for complete removal.

Avoid application in direct sunlight.

**TECHNICAL DATA****COMPOSITION:**

Semi-paste, heavy duty strength

**SHEEN:**

N/A

**% WEIGHT SOLIDS:**

0.7%

**% VOLUME SOLIDS:**

0.7%

**DENSITY (LBS./US GAL.):**

8.54

**VISCOSITY:**

Thick gel

**pH:**

N/A

**COLORS:**

N/A

**ACTION TIME:**

- 15 Minutes -2 hours

**CLEAN UP:**

Soap and water

Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**COVERAGE (SQ. FT./US GAL.):**

N/A

**RECOMMENDED FILM THICKNESS/COAT:**

DO NOT DILUTE

**FLASH POINT:**

N/A

**SHELF LIFE:**

5 Years

**FREEZE/THAW:**

N/A

**CONTAINER SIZES:**

One quart (US) and one gallon (US) containers

**VOC**

0 g/L

**TINTING**

N/A

**SURFACE PREPARATION**

Do not transfer contents to unlabeled bottles or other containers. Read label

carefully before using.

For safety wear latex gloves and eye protection with side shields. On surfaces, other than wood, metal, fiberglass, glass or masonry, test for compatibility in an inconspicuous area.

**WARNING**

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear an NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**APPLICATION**

Apply ZAR® Paint and Varnish Remover liberally using a brush or roller ensuring the entire area to be stripped is covered. Let finish soften until the bare surface can be exposed by gentle scraping. Don't rush – let ZAR® Paint and Varnish Remover do the work. Avoid application in direct sunlight. Check the coating every 15 minutes for ease of removal by gently scraping the surface. Several applications may be necessary depending on the thickness and the age of the coating to be removed. If a second application is required, apply directly over the first coat. On rounded or uneven surfaces the use of an old toothbrush simplifies the removal process. Allow ZAR®



**ACTION TIME:**  
15 Minutes



**CLEAN-UP:**  
Soap and Water



**COVERAGE:**  
1 Application



**SPREAD RATE:**  
Varies on Project

Paint and Varnish Remover to sit on the surface 15 minutes for latex or oil based paints. For polyurethane coatings allow from 15 minutes - 2 hours depending on the type of polyurethane. When the remover has completely penetrated the coating, remove with a scraper or nonabrasive pad. If recoating the surface, wipe with a damp cloth to remove any residual stripper.

\*Two-component epoxy coatings and masonry waterproofing paints may take several applications for complete removal.

### CAUTION

May cause eye or skin irritation. Harmful if swallowed. **Use only with adequate ventilation.** Avoid breathing vapors. Avoid contact with eyes, skin and clothing. Keep container tightly closed, when not in use. Wash thoroughly after handling.

**FIRST AID:** In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean contaminated shoes. If affected by inhalation of vapor, remove to fresh air. If swallowed, do not induce vomiting, get medical attention immediately. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations.

KEEP OUT OF REACH OF CHILDREN.  
PROTECT FROM FREEZING.  
DO NOT TAKE INTERNALLY.

### FIRST AID

**EYES:** Flush immediately with large amounts of water for at least 15 minutes. Take to a physician for medical attention.

**SKIN:** Wash affected areas with soap and water. Consult a physician if irritation persists. Remove contaminated clothing.

**INGESTION:** Seek medical attention. If individual is drowsy or unconscious do not give anything by mouth. Place individual on the left side with the head down. Consult a physician, medical facility or poison control center for advice about whether to induce vomiting.

**INHALATION:** Remove to fresh air.

For additional health and safety information please refer to the "Safety Data Sheet".

### WARRANTY

N/A

### SPECIFICATION

N/A



Paint and Varnish Remover  
1 QT. 6/Case .....40112  
1 GAL. 2/Case .....40113

**DISCLAIMER:** This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of UGL's knowledge, or obtained from sources believed by UGL to be accurate, and UGL does not assume any legal responsibility for use or reliance upon same. Before using any product, read the label.